



Copo Star 96

The concentrated, phosphate- and solvent-free, highly alkaline cleaner for removing heavy soiling such as oils, greases, environmental dirt, graphite dust, rubber abrasion, etc. Due to its soil-repellent properties, it is ideal for workshop floor, industrial, engine and commercial vehicle cleaning (chassis, tarpaulins, etc.) as well as for removing copolymer-based floor sealants. Also optimally suited for biological service water treatment plants. Quick release according to ÖNORM 5106.

page 1 of 1

Areas of use

Workshop floors, alkali-resistant industrial floors, engines, commercial vehicles (chassis, tarpaulins, steel rims etc.)

Recommendations for use

Depending on soiling: Workshop and industrial floor cleaning: 1:15 to 1:60. Engine, truck chassis and tarpaulin cleaning: 1:4 to 1:18 and steel wheel rim cleaning: 1:1 to 1:6 apply over the entire surface, leave to act for a short time and rinse thoroughly with a high-pressure cleaner. Removal of copolymer-based floor sealants: 1:1 to 1:3

Container

Container	Item no.
21 KG	276021
225 KG	276225

pH-value: 12,8

Warnings

Do not use on hot surfaces.;Do not let dry.;Before using, check suitability and compatibility.;

Notice

This product information can advise you only without obligation. Liability on our part can not be derived. Please check whether the product is suitable for your application. We will be pleased to assist you.